



**200W POWER SPLITTER FOR TETRA800 / CDMA800 / GSM900 / PCN1800 / UMTS / WLAN / Wimax / Others**

**Model : SUN-PS-835-200-Y-Z(Z)**

Where

Y is Number of Ways (dB) – 2,3,4

Z(Z) is Connector – N(F), N(M)



Model	SUN-PS-835-200-Y-Z(Z)		
Frequency Range (MHz)	800-3500MHz		
Number Of Ways	2	3	4
Insertion Loss (dB)	0.3	0.3	0.1
Total Loss (Port to Port Loss)*	≤3+0.2	≤4.8+0.4	≤6+0.3
Power Rating (W)	200		
VSWR	≤1.2		
Impedance (Ohm)	50		
3rd Order Intermodulation (dBc)	≤-140		
Temperature (deg)	-35 ~ 60		
Humidity (%)	6 ~ 95		
Water Proof	IP65		
RF Connector	N (F) or Others		
Size (mm)	215 x Ø20 x 60	230 x Ø18 x 60	230 x Ø18 x 60
Weight (g)	250	300	340
Color	Black		

\* The measurement is adding 15dB external Attenuator in the Network Analyzer

Technical data are subjected to change without notice – File: SUN-PS-835-200-Y-Z(Z) 2008V2.0